

SPECIFICATIONS

SUPPORTED DEVICE	iPhone14, 13, and 12/Pro iPhone SE 3rd/2nd Gen, iPhone 8/7 iPod Touch 7th/6th/5th Gen
INTERFACES	Apple lightning connector (MFi) USB Type-C (Charging)
BATTERY	Li-ion, 1100 mAh
BUTTONS	Two scanning buttons
INDICATORS	Multiple color LEDs
BARCODE TYPES	UPC/EAN/JAN, GS1 DataBar, Code 39, Code 128, Code 32, Code 93, Codabar/NW7, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, MSI, Telepen, Trioptic, China Post QR Code, Micro QR Code, PDF417, MicroPDF417, GS1 Composite, Aztec Code, Data Matrix, MaxiCode, Han Xin Code Postal: Intelligent Mail Barcode, Postal-4i, Australian Post, British Post, Canadian Post, Japanese Post, Netherlands (KIX) Post, Postnet, Planet Code OCR Option: OCR-A, OCR-B, E13B (MICR)

NUMBER OF SCAN	> 20,000 scans/charge
CHARGING	5V/2A Minimun 5V/3A Recommended
POWER CONSUMPTION	Peak 2W, Operation 1.4W, Idle 0.18W
CERTIFICATIONS	Battery: IEC 62133: 2012 (Second Edition) EMC / EMI: FCC, Part 15 Subpart B ICE-003 KN32, KN35 KN61000-4-* (IEC61000-4-*) Safety: IEC 60825-1 Ed 2 (2007)
OPERATION	Discharge: -10°C~40°C / 14~103°F Charge: 0~40°C / 32~103°F
IP RATING	IP67 (Optional)
COUNTRY OF ORIGIN	TAIWAN



iPod Touch 7th/6th/5th Gen



iPhone SE 3rd/2nd Gen, iPhone 8/7



iPhone 14, 13, and 12/Pro

