

## SPECIFICATIONS

<b>SUPPORTED OS</b>	iOS, iPadOS	<b>NUMBER OF SCAN</b>	> 20,000 scans/charge
<b>INTERFACES</b>	Apple lightning connector (MFi) USB Type-C	<b>CHARGING</b>	5V/2A Minimum 5V/3A Recommended
<b>BATTERY</b>	Li-ion, 1100 mAh	<b>POWER CONSUMPTION</b>	Peak 2W, Operation 1.4W, Idle 0.18W
<b>BUTTONS</b>	Four scanning buttons	<b>CERTIFICATIONS</b>	Battery: IEC 62133: 2012 (Second Edition) EMC / EMI: FCC, Part 15 Subpart B ICE-003 KN32, KN35 KN61000-4-* (IEC61000-4-*) Safety: IEC 60828-1 Ed 2 (2007)
<b>INDICATORS</b>	Multiple color LEDs	<b>OPERATION</b>	Discharge: -10°C~40°C / 14~103°F Charge: 0~40°C / 32~103°F
<b>BARCODE TYPES</b>	UPC/EAN/JAN, GS1 DataBar, Code 39, Code 128, Code 32, Code 93, Codabar/NW7, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, MSI, Telepen, Trioptic, China Post  QR Code, Micro QR Code, PDF417, MicroPDF417, GS1 Composite, Aztec Code, Data Matrix, MaxiCode, Han Xin Code  Postal: Intelligent Mail Barcode, Postal-4i, Australian Post, British Post, Canadian Post, Japanese Post, Netherlands (KIX) Post, Postnet, Planet Code  OCR Option: OCR-A, OCR-B, E13B (MICR)	<b>IP RATING</b>	IP67 (Optional)

